



Technical Data

Operating Conditions

Medium

Density

min 0.75 g/cm³

	g/cm ³

Pressure/Temperature

Op. Pressure Type 25470 max. 10 bar g
 Type 25480 max. 2,5 bar g
 Type 25490 max. 2,5 bar g

	bar g
	bar g
	bar g

Design Pressure

	bar g
--	-------

Op.Temp. Type 25470 max. 140 °C
 Type 25480 max. 80 °C
 Type 25490 max. 60 °C

	°C
	°C
	°C

Design Temperature

	°C
--	----

Indication Rail

Version

Makrolon
 Makr. with protection tube
 Alu flaps red

<input type="checkbox"/>
<input type="checkbox"/>
<input type="checkbox"/>

Material

Float chamber (wetted parts) PVDF resp. PP resp. PVC
 Float PVDF resp. PP resp. PVC

Dimensions

Connection distance Dimension " L "

	mm
--	----

Flange Connections

Flange connection with saddle flange and bushing
 Standard/Nom.Pressure VSM 18696/PN10
 DIN 8063/PN10
 Nom.Diameter (Standard) DN 15-32

DN

Accessories

Magnetic Switch
 Transmitter
 Control unit/voltage

Number	Type
Type	Indication length mm
Volt	AC / DC Type

Additional Accessories acc. attached sheet

<input type="checkbox"/>
